

Distribuidores

Mecânicos

MASTER D



3000 D



5500 D



7500 D



10000 D

Características	3000 D	5500 D	7500 D	10000 D
Volume de carga (m³)	1,8	2,8	3,75	5,3
Capacidade de carga (kg)	3000	5500	7500	10000
Altura (mm)	1645	1860	1945	2145
Largura (mm)	1790	1850	1920	2200
Comprimento (mm)	3955	4955	4955	5080
Bitola (mm)	1440	1560	1620	1800
Rodado	Fixo	Balancin	Balancin	Balancin
Roda	Aro 16" x 5,50	Aro 16" x 5,50	Aro 16" x 6,00	Aro 13" x 15,5
Pneu	7,50 x 16"	7,50 x 16"	9,00 x 16"	400/60 15.5
Aplicação de Calcário (L/ha)	100 a 21600	100 a 21600	100 a 21600	100 a 21600
Vazão Regulável (L/min)	15 a 2400	15 a 2400	15 a 2400	15 a 2400
Faixa de distribuição (m)	7 a 15	7 a 20	7 a 20	7 a 20
Largura de esteira (mm)	400 e 800	400 e 800	400 e 800	400 e 800
Peso (kg)	1065	1453	1541	1930
Potência no motor (cv)	50	75	90	90
Kit direcionador				
Abafador				
Opcional de pneu				



Distribuidores

Semi Hidráulicos

MASTER DH1



5500 DH1



7500 DH1



OPCIONAL COM PNEU 14.9 X 28



OPCIONAL COM BITOLA REGULÁVEL (BR)



10000 DH1

OPCIONAL COM BITOLA REGULÁVEL (BR)



12000 DH1

Características	5500 DH1	7500 DH1	10000 DH1	12000 DH1
Volume de carga (m³)	2,8	3,75	5,3	7
Capacidade de carga (kg)	5500	7500	10000	12000
Altura (mm)	1830	1950	2145	2540
Largura (mm)	1900	1900	2200	3690
Comprimento (mm)	4955	4955	5080	6100
Bitola (mm)	1560	1620	1800	1400 a 3000
Rodado	balancin	balancin	balancin	Regulável
Roda	Aro 16" x 5,50	Aro 16" x 6,00	13" x 15,5	w09l x 18"
Pneu	7,50 x 16"	9,00 x 16"	400/600x15,5	12,5/80 x 18"
Aplicação de Calcário (L/ha)	100 a 21600	100 a 21600	100 a 21600	100 a 21600
Vazão Regulável (L/min)	15 a 2400	15 a 2400	15 a 2400	15 a 2400
Faixa de distribuição (m)	7 a 20	7 a 20	7 a 20	7 a 20
Largura de esteira (mm)	400 e 800	400 e 800	800	400 e 800
Vazão Hidráulica (Trator) mínima / Máxima (L/min)	45 a 60	45 a 60	55 a 65	55 a 70
Peso (kg)	1493	1527	1901	2688
Potência no motor (cv)	75	90	90	100

Kit direcionador | Bica central

Abafador



www.piccin.com.br

Acesse o QR Code e confira mais **Utilitários**